

PHASE AQUEUSE



PURPOSE

Impression with a base of mixed binders in aqueous dispersion for sound, coated, or bare walls and ceilings.

Matt white stipple finish.

ADEQUA PRIM can be covered with any paint finish or ornamental coating in aqueous or solvent phase, wallpaper, and wall covering.

SURFACES

- Usual building bases conveniently prepared.
- Plasters and derived products, dry wall systems.
- Concrete and derived products.
- Old adherent paints in good condition.

MAIN FEATURES

- Evens the surface's absorption differences for an optimal result.
- Prevents shading phenomena.
- Unspoonifiable.
- Easy use (smooth application, good spreading of the product, no sagging).
- Quick drying, recoatable within the day.

IDENTIFICATION CHARACTERISTICS

In accordance with official standards or, if none applicable, with internal standards.

Aspect	Semi-thick paint.
Dry Matter	In weight: 68 ± 2 %. In volume: 47 ± 2 %.
Density	1.66 ± 0.05
Flash Point	n/a.
VOC Concentrations	Max. 5 g/l. EU threshold value for this product (A/h cat.): 30 g/l.
Drying Time (20°C, 65% RH)	Dry: 30 min. Recoatable: 2 hrs with an aqueous finish. <i>Drying delayed by cold and damp weather.</i>
Covering	5 to 7 sqm/l depending on the nature and condition of the surface.
Classification	NF T36-005: Family I Class 7b2. Indoor air emissions* : A+. <small>* Information about the indoor emission level of volatile substances presenting a toxicity hazard through inhalation on a scale ranging from A+ (very low emissions) to C (high emissions).</small>
Colours	White. May be tinted through addition of universal colouring matter without exceeding 3 %.
Packaging	16 L

USE

Surfaces, preparatory work, and application conditions must comply with the applicable standards/DTU (French standards).

Base Preparation

Bases must be sound, dry, cohesive and consistent with the product application.

- **Bare bases:** gin, brush and dust thoroughly.
 - **Painted bases:** remove non-cohesive parts, leach, matt the glossy surfaces, clean thoroughly, dry.
 - **Difficult bases:** Use preferably ERMO PRIM.
- Surface rendering and overhauling works depending on the desired finish.

Product Application

Process

1 to 2 regular coats, depending on use (impression or multi-layer).

Equipment

Anti-drop roller, brush, spray gun.

Dilution

Product ready for use.

Up to 5 % water over absorbent bases or by mechanical application.

Equipment Cleaning

WATER, immediately after use.

Application Conditions

- Ambient and surface temperature above 5°C (caution if T > 35°C).
- Relative humidity below 80 %.
- Dry weather, sheltered from strong winds and direct sunlight.

CONSERVATION

- 24 months in original unopened packaging.
- Store away from frost and temperatures above 35°C.

HEALTH, SAFETY, AND ENVIRONMENT

Refer to

- The safety information label on the packaging.
- Safety Data Sheet (Fiche de Données de Sécurité) on the INTERNET: www.zolpan.fr

IMPORTANT NOTICE REGARDING THE ZOLPAN TECHNICAL SHEETS: This version cancels and supersedes previous editions. It is our customers' responsibility to check that they have the latest edition before using the product. The information given in this sheet only has an indicative value and cannot replace the specific data relating to the type and condition of the surface to be treated.



Zolpan sas : 17 quai Joseph Gillet - 69316 Lyon cedex 04 - Tél: 04 72 10 70 60 - Fax: 04 72 10 70 73
www.zolpan.fr - SIREN : 972 503 387 - N° RCS : 972 503 387 RCS LYON - CAPITAL SOCIAL : 6 127 440 €