

PHASE AQUEUSE



PURPOSE

Powerful degreasing product especially suited for the in-depth cleaning of diverse greasy or very dirty surfaces (before renovation or re-painting for instance): oily residues, grease, soot, sludge, rubber, tar, atmospheric pollutions...

Thanks to its specific formulation (solvent-free), NETTOYANT MULTIUSAGES is a product with great use versatility.

Several examples of use:

- Cleaning of façades, roofs and greasy or very dirty floors: factories, industrial kitchens, car parks, workshops, garages, oil manufactures, agro-industry...
- Washing of painted floors, for instance with epoxy paint (factory floors, for example).
- Cleaning of materials of all kinds: vehicles, agricultural material, processing machines, wagons, engines...
- Cleaning of stones, interlocking paving blocks, bricks...
- Degreasing of oily metals.
- Leaching of paints, matting of pre-painted surfaces, stripping of bills...
- Cleaning of soot in air conditioning, heating systems.
- Cleaning of blinds, tarpaulins...

SURFACES

- Concrete and derived products, tiles, slate.
- Metals and alloys.
- Stone, bricks, tiles, earthenware, marble.
- Old paints.
- Plastic materials such as PVC, artificial leather, Buflon, Somvyl, simili, thermoplastic floor tiles, laminated floors...

IMPORTANT: If in doubt, proceed to a prior insensibility test to the treatment of the material. Adapt the use concentrations if necessary.

MAIN FEATURES

- Descales and emulsifies greasy dirt.
- Eases the adherence of paint finishes.
- Easy to rinse (non-foaming).
- Inert in relation to painted materials and surfaces (adapted concentration).
- Water-soluble in all proportions.

IDENTIFICATION CHARACTERISTICS

In accordance with official standards or, if none applicable, with internal standards.

Aspect	Red liquid, nice fragrance. Combination of alkaline, tensides, and emulgator.
Density	1.10 ± 0.02
pH (pure product)	Ca. 14.
Flash point	n/a.
Average Coverage	10 to 30 sqm per litre of concentrated product, depending on the nature of the operations.
Classification	NF T36-005: Not classified.
Packaging	Plastic can: 5 L - 20 L

USE

Surfaces, preparatory work and application conditions must comply with the applicable standards/DTU (French standards).

Dilution

NETTOYANT MULTIUSAGES is delivered in a concentrated form, which should be diluted with water, depending on the works (clogging, frequency of cleaning).

Average use concentration (preliminary test if necessary):

- Regular cleaning (painted floors, tiles, plastic materials): 1 vol. for 30 vol. water.
- Irregular or difficult cleaning (rolling material, greasy floors), matting of the paints, pre-painted surfaces: 1 vol. for 10 to 20 volumes water.
- Automatic washer, HP cleaning: 2 to 3 % at lance output.

Warm water will ease the cleaning process (ideal temperature: 40 to 50°C).

Equipment

- Automatic washer, monobrush.
- Atomizer, watering-can.
- Brush, nylon broom, synthetic sponge.
- HP cleaner.

Use Instructions

- Dilute the product to the necessary concentration.
- Spread the solution uniformly over the surfaces to be cleaned and let it work a few minutes, depending on the degree of clogging.
- Activate the cleaning with a broom or brush if necessary. Do not let dry.
- Vacuum-clean, rinse abundantly with water (under pressure when possible).
- Repeat the treatment if necessary.
- Let dry before painting.

Equipment Cleaning

WATER, immediately after use.

Practical Advice

- Clean immediately or rinse abundantly with water any projections and running onto surrounding surfaces, for which the treatment does not apply.
- Protect metals with an anti-rust product as quickly as possible after the treatment.

CONSERVATION

- 24 months in original unopened packaging.
- Store in a cool and ventilated room.

HEALTH, SAFETY, AND ENVIRONMENT

Refer to

- The safety information label on the packaging.
- The Safety Data Sheet (Fiche de Données de Sécurité) on the INTERNET: www.zolpan.fr

IMPORTANT NOTICE REGARDING THE ZOLPAN TECHNICAL SHEETS: This version cancels and supersedes previous editions. It is our customers' responsibility to check that they have the latest edition before using the product. The information given in this sheet only has an indicative value and cannot replace the specific data relating to the type and condition of the surface to be treated.



Zolpan sas : 17 quai Joseph Gillet - 69316 Lyon cedex 04 - Tél: 04 72 10 70 60 - Fax: 04 72 10 70 73
www.zolpan.fr - SIREN : 972 503 387 - N° RCS : 972 503 387 RCS LYON - CAPITAL SOCIAL : 6 127 440 €