



## SUNCOAT adherence activator Non film-forming Colourless

**PURPOSE** Reagent organic-silicic primer in alcohol solution aimed at improving the adherence of SUNCOAT over vitrified materials

**SURFACES** Glass, glass paving blocks, stoneware

**MAIN FEATURES**

- \* Excellent adhesion base for vitrified surfaces by creation of a chemical binding chimique
- \* One-pack ready-for-use product
- \* Fast drying

**IDENTIFICATION CHARACTERISTICS** In accordance with official standards or, if none applicable, with internal standards

<b>Aspect</b>	Colourless fluid liquid
<b>Dry matter</b>	* in weight: 3 % * in volume: 3 %
<b>Density</b>	0.80 ± 0.02
<b>Flash point</b>	Below 21°C
<b>Dry time</b>	Dry: 15 mn
<b>(20°C, 65 % RH)</b>	Recoat: minimum 30 mins / maximum 2 hrs Beyond this time, recoat
<b>Coverage</b>	About 15 sqm/l (60 g/sqm)
<b>Classification</b>	NF T36-005: Family I Class 10 i

**USE** Surfaces, preparatory work and application conditions must comply with the applicable standards/DTU (French standards)

**BASE PREPARATION** Bases must be sound, dry, cohesive and consistent with the product application

Thorough cleaning and degreasing of the surfaces with alcohol or with an alkaline detergent such as NETTOYANT MULTIUSAGES, rinsing, drying

### PRODUCT APPLICATION

**Process** Spread the product to saturation with a sponge, cloth or mop, depending on the site's possibilities

Let it dry (about 30 mins by 20°C) and recoat rapidly with the SUNCOAT varnish at least within 2 hours after its application

Beyond this time, the action of the PRIMAIRE SUNCOAT is cancelled and requires new treatment

**Dilution** Ready-for-use product

Shake before use (VERY IMPORTANT)

**Equipment cleaning** WATER, immediately after use

**Practical advice**

- \* Application conditions:
  - . Ambient and surface temperature above 5°C (caution if T > 35°C)
  - . Relative humidity below 90 %
  - . Dry and condensation-free surface
  - . Sheltered from wind and direct sunlight
- \* Respect the recoat time between layers

**COLOURS** Colourless - Non film-forming

---

**PACKAGING** 1 L - 4 L

---

**CONSERVATION** 12 months in unopened original packaging  
Store in a cool and ventilated place

---

**HEALTH AND SAFETY** Refer to:  
\* The safety information label on the packaging  
\* Safety Data Sheet (Fiche de Données de Sécurité) on the INTERNET: [www.zolpan.fr](http://www.zolpan.fr)

---

Technical Data Sheet n° 5105

**Issue date: June 1994**

**Last modified: June 2012**

*NB: Cancels and supersedes previous editions. It is our customers' responsibility to check that they have, the latest version before using the product.*

*The information given in this sheet only has an indicative value and cannot replace the specific data relating to the type and condition of the surface to be treated.*