



Repair product for waterproofing faults
Applicable by any weather, on all surfaces (even moist)
Ready-for-use, rapidly impervious to rain,
immediate action
Great flexibility of the film
Good resistance to UV rays and weathering
Grey rubber finish

PURPOSE Product for the punctual repair of waterproofing faults recommended for "emergency" interventions over almost every surface and traditional building works: covers, gutters, downpipes, piping, chimney stacks, terrace roofs, etc.
 Applicable by any weather and on all surfaces, even moist. Immediate effect. Ready for use.
 Once dry, provides a grey, satin matt rubber film which is waterproof and resistant to atmospheric aggressions
 May remain as it is or be coated with a REVALPA coating

SURFACES Usual building surfaces: waterproofing concrete, multi-coat, shingles, rigid PVC, metals, glass, wood, roofing, polyester, etc.

MAIN FEATURES

- * Waterproof rubber film
- * Ready for use
- * Direct adherence on all usual building surfaces (even moist)
- * Rapid and simple intervention, without any prior impression of the surface
- * Immediate action
- * Very good resistance to atmospheric aggressions and UV rays
- * Great film flexibility
- * Free from asphalt or bituminous derived substances
- * May remain as it is or be coated

IDENTIFICATION CHARACTERISTICS **In accordance with official standards or, if none applicable, with internal standards.**

Aspect Thick paste, high polymers based in solvent phase

Dry matter * in weight: 50 ± 2 %
 * in volume: 46 ± 2 %

Density 1.05 ± 0.05

Flash point > 38°C

VOC concentrations Max. 485 g/l. EU threshold value for this product (cat.A/i): 500 g/l

Dry time (20°C, 65 % RH) Impervious to rain: immediately
 Recoatable: minimum 72 hrs

Average consumption 2 to 3 kg/sqm for local repairs

Classification **NF T36-005:** Family I class 7 b1

USE Surfaces, preparatory work and application conditions must comply with the applicable standards/DTU (French standards).

BASE PREPARATION Bases must be sound, cohesive and consistent with the product application.
* Thorough removal of dust, mud, moss, dry leaves, greasy deposit and all dirt likely to prevent the adherence
* Direct application of the product

PRODUCT APPLICATION

Process One thick and regular coat
Reinforcement possible after repairing, in particular along the cracks, with a braid of membrane such as ULTRATEX rubbed in between 2 coats of REPARCOAT
Covering possible with any REVALPA roof coating

Equipment Scraper, painter's knife, brush

Dilution Product ready for use

Equipment cleaning DILUANT R or REX, immediately after use

COLOURS Grey

PACKAGING 1 kg - 5 kg - 20 kg

CONSERVATION 24 months in unopened original packaging
Store in a dry, cool and ventilated room

HEALTH AND SAFETY Refer to:
* The safety information label on the packaging
* Safety Data Sheet (Fiche de Données de Sécurité) on the INTERNET: www.zolpan.fr

Technical Data Sheet n° 2165

Issue date: January 1995

Last modified: June 2012

NB: Cancels and supersedes previous editions. It is our customers' responsibility to check that they have, the latest version before using the product.

The information given in this sheet only has an indicative value and cannot replace the specific data relating to the type and condition of the surface to be treated.